B431 Specifications





Productive, high performance mono printers for everyday use

If you need a black & white printer that supports the highest levels of office productivity – without straining your budget – you need the B431. Built for speed and maximum efficiency, it produces the first printed page in less than 5 seconds and the rest at an impressive 38 pages per minute. And that's just the start.

Choose the B431d for fast individual printing or the B431dn for sharing on the office network saving costs without losing productivity

Designed for productivity

Of course, there's more to productivity than fast print speeds. The true 1200 x 1200dpi resolution delivers fine, crisp detail which is generously supported by a powerful 330MHz processor and 64MB of memory (expandable to 320MB), and a paper supply that can be increased to 880 sheets to mirror your productivity demands. There's even a 100-sheet multi-purpose tray, supporting a range of paper sizes, to meet everyday office printing requirements. Plus, it comes with OKI Template Manager – making it easy for you to create and print a wide variety of office documents.

Maximum Efficiency

The compact design of the B431 means it can be placed on any desktop within your office. What's more, its high yield consumables let you print up to 10,000 pages without replenishment, helping to keep the cost-per-page down whilst maximising your uptime. Other essential features include automatic two-sided printing as standard, a 'Power Save' mode that reduces energy consumption to just 8W, and because the toner cartridge and drum are all separate, you only ever have to replace what needs replacing. The B431dn also comes with our popular PrintSuperVision software - the smart way to actively manage your office printing, for improved control by tracking and monitoring usage of your networked printers.

Built for endurance

Maximum reliability means maximum return on investment. And that's what the B431 delivers. It uses ultra-reliable digital LED technology (pioneered by OKI and proven over more than 20 years) with fewer moving parts for exceptional durability.

Exceptional value for money

Not only does the B431 give you much more for your money, but it's surprisingly inexpensive to run. High yield consumable and built-in reliability all contribute to a low total cost of ownership

A4	~
Range of media handling	~
Mono	¥
Print	~
1-5 users	~





B431 - Mono Printers

	TYPEFACES		
38ppm mono	Printer fonts	87 scaleable PCL and 136 PostScript fonts, 2 bitmap fonts,	
Less than 5 seconds		OCR-A/B Epson FX and IBM PPR at various pitches	
Approx. 20 seconds from power save	Dot matrix fonts	12 types of one dimension with 28 variations: UPC-A, UPC-E,	
330MHz PowerPC405	Barcode	EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4POSTNET, Customer barcode, USPS Zip Barcode, 1 type of two dimension: PDF417	
B431d: IEEE1284 Bi-directional parallel, Hi-Speed USB 2.0	PRINT QUALITY		
B431dn: IEEE1284 Bi-directional parallel, Hi-Speed USB 2.0, 10/100BaseTX Ethernet	Resolution	1200 x 1200dpi	
PCL5e, PCL6, Epson FX, IBM ProPrinter, PostScript3 emulation	GENERAL FEATURES		
10/100BaseTX Ethernet card with internal web server for printer and network card set-up and management. Includes SMTP mail client for alerts. All major network protocols supported - TCP/IP, Netware, Ethertalk and NetBEUI. TCP/IP: ARP, IPv4/v6, ICMPv4/ v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, AutoIP, SNMPv1/v3, DNS, DDNS, uPnP, Bonjour, WINS, SSL/TLS, SMTP, JetDirect protocols; Netware 3.x, 4.x, 5.x, and 6 with full NDS and NDPS support:- QServer over IP and IPX, R-Printer, N-Printer, NCP, SPX, IPX, SAP, RIP; Ethertalk: ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP; NetBEUI: SMB, NetBIOS; Other:	Memory	Standard RAM: 64MB; Maximum RAM: 320MB	
	Environment	Operating temperature/ humidity: 10°C to 32°C/ 20% to 80% RH non-condensing	
		Storage temperature/humidity: -10°C to 43°C, 10% to 90% RH non-condensing	
	Power supply	230 VAC +/- 10%, 50 or 60Hz +/-2%	
	Power consumption	Typical: 550W; Max: 900W; Idle: 70W; Power Save: 8W	
Windows 2000 / 2003 / 2003 x64 / XP / XP x64 / Server 2008 OS Compatibility1 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Vista (32-bit & 64-	Noise level	Operating: 54dB(A) or less; Standby: 30dB(A) or less; Power save: Background Level	
	Dimensions (HxWxD)	244.5 x 387 x 364mm	
	Weight ³	12kg	
Download Utility, Print Control Server ² , Print Control Client, Storage Device Manager ²	Duty cycle	Maximum: 80,000 pages/month; Recommended: 5,000 pages/month	
B431dn: Template Manager ² , Print Control Server ² , Print Control Client, PrintSuperVision.net ² , OKI LPR ² , Network Extension, Network Card Setup, Configuration Tool ² , Op-Panel Download Utility, Storage Device Manager ²	Warranty	1 year	
	Product order numbers	B431d: 44566305 ; B431dn: 44566325	
	Accessories (Order Numb	ers)	
Trav 1: 250 sheets of 80gsm: Multi-nurnose trav: 100 sheets	2nd paper tray	44575702	
of 80gsm	Memory	64MB: 44615402; 256MB: 44615411	
Tray 2: 530 sheets of 80gsm	Consumables (Order Numbers)		
880 sheets of 80gsm	Black toner cartridge*		
Tray 1: A4, A5, B5(JIS), A6, Letter, Legal 13, Legal 14, Executive, Statement; Tray 2: A4, A5, B5(JIS), Letter, Legal 13, Legal 14,	(3,000 pages)	44574702	
Executive; Multi-purpose tray : A4, A5, B5(JIS), A6, Letter, Legal 13, Legal 14, Executive, Statement, Envelopes: Monarch, Com-9, Com-10, DL, C5, C6; Duplex : A4, B5(JIS), Letter, up to	(10,000 pages) Image drum**	44574902	
Tray 1/2: 60 to 120gsm; Multi-purpose tray: 60 to 163gsm;	., . , . , . ,	 	
Standard	 Toner: Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 2,000 pages yield compliant with ISO/IEC 19752. 		
	** Drum: 3 pages per job		
	Less than 5 seconds Approx. 20 seconds from power save 330MHz PowerPC405 B431d: IEEE1284 Bi-directional parallel, Hi-Speed USB 2.0 B431dn: IEEE1284 Bi-directional parallel, Hi-Speed USB 2.0, 10/100BaseTX Ethernet PCL5e, PCL6, Epson FX, IBM ProPrinter, PostScript3 emulation 10/100BaseTX Ethernet card with internal web server for printer and network card set-up and management. Includes SMTP mail client for alerts. All major network protocols supported - TCP/IP, Netware, Ethertalk and NetBEUI. TCP/IP: ARP, IPv4/v6, ICMPv4/ v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, AutoIP, SNTP, Windows Rally(WSD-Print, LLTD), SLP, NetBIOS over TCP, JetDirect protocols; Netware 3.x, 4.x, 5.x, and 6 with full NDS and NDPS support:- QServer over IP and IPX, R-Printer, N-Printer, NCP, SPX, IPX, SAP, RIP; Ethertalk: ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP; NetBEUI: SMB, NetBIOS; Other: EAP Windows 2000 / 2003 / 2003 x64 / XP / XP x64 / Server 2008 (32-bit & 64-bit); Linux PPD; Mac OS 10.3.9 or greater B431d: Template Manager ² , Print Control Server ² , Print Control Client, PrintSuperVision.net ² , OKI LPR ² , Network Extension, Network Card Setup, Configuration Tool ² , Op-Panel Download Utility, Print Control Server ² , Print Control Client, PrintSuperVision.net ² , OKI LPR ² , Network Extension, Network Card Setup, Configuration Tool ² , Op-Panel Download Utility, Storage Device Manager ² Fray 1: 250 sheets of 80gsm 880 sheets of 80gsm Tray 1: 4.4, A5, B5(JIS), A6, Letter, Legal 13, Legal 14, Executive, Statement; Tray 2: A4, A5, B5(JIS), A6, Letter, Legal 13, Legal 14, Executive, Statement; Tray 2: A4, A5, B5(JIS), A6, Letter, Legal 13, Legal 14, Executive, Statement; Tray 2: A4, A5, B5(JIS), A6, Letter, Legal 13, Legal 14, Executive; Statement; Tray 2: A4, A5, B5(JIS), A6, Letter, up to Legal 14, Executive Tray 1/2: 60 to 120gsm; Multi-purpose tray: 60 to 163gsm; Duplex: 60 to 120gsm	38ppm mono Printer fonts Less than 5 seconds Dot matrix fonts Approx. 20 seconds from power save 300Ht/2 PowerPC405 B431d: IEEE1284 Bi-directional parallel, Hi-Speed USB 2.0 Dot matrix fonts B431d: IEEE1284 Bi-directional parallel, Hi-Speed USB 2.0 PRINT QUALITY B431d: IEEE1284 Bi-directional parallel, Hi-Speed USB 2.0 Resolution 10/100BaseTX Ethernet Memory PCLSe, PCL6, Epson FX, IBM ProPrinter, PostScript3 emulation Memory 10/100BaseTX Ethernet Memory Clent for alers, All major network protocols supported - TCP/IP, Netware, Ethertalk and NetBEUI. TCP/IP: APR, IPVA/v6, ICMPV4// v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, AutoIP, SNTP, Windows Rall/(WSD-Print, LTD), SLP, NetBIOS over TCP, EAP Power supply Norise level Noise level Noise level Mindows 2000 / 2003 / 2003 x64 / XP / XP x64 / Server 2008 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Vista (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Vista (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Vista (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Server 2008 R2 (64-bit) / Vista (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Server 2008 R2 (64-bit) / Vista (32-bit & 64-bit) Dimensions (HxWxD) Metwork Card Setup, Configuration Tool ² , Op-Panel Download Utility, Print Control Server ² , Print Control Ray 1: z50 sheets of 80gsm Zod paper	

¹Check local OKI Printing Solutions website for latest driver releases and OS compatibility; ²Windows only; ³Including all consumables

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI Printing Solutions toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

OKI PRINTING SOLUTIONS POLAND

Domaniewska str. 42 02-672 Warsaw Tel: +48 (0) 22 44 86 500 Fax: +48 (0) 22 44 86 501 www.oki.pl



