



Consistent colour. Stand out results. Superior media flexibility

So when it comes to choosing an A3 colour printer, it makes sense to invest in a machine that will consistently and dependably deliver high quality output. For a surprisingly modest investment, you get superior media flexibility, impressive performance, and exceptional ease of use and the proven reliability of digital LED printing technology. In other words, the C910 really is a printer you can rely on.

Consistent colour

The C910 produces stunning quality with remarkable consistency.

- ProQ2400 multi-level 1200 x 600dpi print resolution
- Microfine High Definition 15,000- page toner and high precision image drums
- In-built Graphic Pro colour management firmware for colour matching and managing ICC profiles
- Compatible with EFI Colorproof XF colour management RIP and EFI Fiery XF production RIP software

Superior media flexibility

With the C910 you can print on a huge range of media, including specialist structured paper.

- Paper sizes from A6 to oversized A3 and SRA3, plus 328 x 1200mm banners
- Print on stock from 64 to 300gsm
- Automatic two-sided printing on media up to 188gsm
- Optional paper trays increasing capacity up to 2,880 sheets

Impressive performance

When the pressure is on the C910 really earns its keep.

- Get more done, faster; with A3 print speeds of 16ppm in colour and 20ppm mono (up to 31ppm in colour and 36ppm mono for A4)
- Generous 512MB RAM as standard
- Standard 40GB Hard Disk Drive for storing job data
- 800MHz processor

Total ease-of-use

The C910's controls are intuitive and easily mastered.

- Auto Media Detect for automatically detecting and selecting appropriate paper weight
- Auto Print Density and Colour Registration Control to ensure accurate colour reproduction
- Easy to use bypass tray for trouble-free insertion of special media
- Optional finisher for automatic hole-punching, folding, saddle stitching and booklet making

Dependability

The C910 lets you get more done with fewer interruptions.

- Simple, flat paper path for trouble-free operation
- The product of more than 30 years experience of manufacturing robust printing solutions
- Digital LED technology for ultra-reliable printing
- Free, three-year parts and labour warranty extension available

A4/A3/A3+/SRA3	✓
Range of media handling	✓
Colour, Mono	✓
Print	✓
1 - 5 users	✓

Variants available:
C910n
networked
C910dn
duplex, networked



C910 - Colour and Mono Printer

PRINTER	
Print speed	A4: 31ppm colour, 36ppm mono; A3: 16ppm colour, 20ppm mono
Time to first print	10.5 seconds colour, 9 seconds mono
Warm up time	85 seconds or less from power on
Processor speed	PowerPC 750 800MHz
INTERFACE AND SOFTWARE	
Connectivity	IEEE 1284 Bi-directional Parallel, Hi-Speed USB 2.0, 10Base-T/100Base-TX/1000Base-T Ethernet
Printer languages	PCL5c, PCL XL (Colour), Adobe PostScript 3 with direct PDF Printing (v1.6), SIDM
Network & protocols	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IP: ARP, RARP, IPv4/v6, ICMPv4/v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, SNMPv1/v3, DNS, DDNS, UPnP, Bonjour, WINS, SSL/TLS, SMTP, POP3, SNTp, WSDPrint, JetDirect protocols. NetWare 3.x, 4.x, 5.x and 6 with full NDS and NDPS support:- PServer, RPrinter, NDPS supported via dedicated OKI NDPS Gateway. AppleTalk:- ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP. NetBEUI:- SMB, NetBIOS. Other:EAP
OS Compatibility¹	Windows Vista (32-bit & 64-bit) / 2000 Workstation (SP3 or later) / 2000 Professional (SP3 or later) / Server 2000 (SP3 or later) / Advanced Server 2000 (SP3 or later) / XP Professional / XP Professional x64 / XP Home / Server 2003 / Server 2003x64 / Server 2008 / Server 2008x64 / Server 2000 (SP4) + Citrix MetaFrame XP Presentation Server Feature Release 4 / Server 2003 Standard Edition + Citrix MetaFrame XP Presentation Server Feature Release 4; Mac OS X 10.3 - 10.6.1
Advanced networking and security	IPv6, 802.1x authentication, SNMPv3, SSL3/TLS HTTPS encryption, Data Encryption, MAC filtering, IP filtering, Secure Erase, Secure Print
Utility Suite¹	Print Control Server², Print Control Client, PrintSuperVision.net², Template Manager², Storage Device Manager², Profile Assistant², Color Correct, PS Gamma Adjuster, PDF Direct Print
TYPEFACES	
Printer fonts	86 scalable PCL fonts, 1 bitmap font, 10 TrueType fonts, 136 Adobe PostScript Type 1 fonts
Barcode	Barcode with Checksum support
PRINT QUALITY	
Resolution	ProQ2400 Multi-level technology, 1200 x 600dpi
Enhancements	Auto Colour Balance, Auto Registration, Auto Media Detect
PAPER HANDLING	
Paper capacity	Tray 1: 530 sheets of 80gsm; Multi-purpose tray: 230 sheets of 80gsm
Paper capacity optional trays	Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm; High Capacity Feeder: 1,590 sheets of 80gsm
Maximum paper capacity	2,880 sheets of 80gsm
Paper sizes	Tray 1/2/3: A3, SRA3 (up to 328 x 457mm), A4, A5, A6; Multi-purpose tray: A3, SRA3 (up to 328 x 457mm), A4, A5, A6, Custom size: Width 79.2 - 328mm Length 90 - 1,200mm; High Capacity Feeder: A3, SRA3 (up to 328 x 457mm), A4, A5, A6
Paper weight	Tray 1/2/3: 64 to 216gsm; Multi-purpose tray: 64 to 300gsm; Duplex: 64 to 188gsm; High Capacity Feeder: 64 to 216gsm
Duplex	Standard: C910dn; Optional: C910n
Paper output	500 sheets face down tray, 200 sheets face up tray

¹ Check local OKI Printing Solutions website for latest driver releases and OS compatibility;
² Windows only;
³ Including all consumables;

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI Printing Solutions toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as “compatible”, and if it does work, your printer's performance and print quality may be degraded.

GENERAL FEATURES		
Memory	Standard: 512MB; Maximum: 1024MB Hard Disk Drive: 40GB	
Operating conditions	Temperature/Humidity: 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended) Storage: -20°C to 45°C, 10% to 90%RH	
Power supply	Single phase 220 to 240VAC, frequency 50Hz +/- 2Hz	
Power consumption	Typical: 750W; Max: 1500W; Idle: 200W (average); Power Save: <33W	
Noise level	Operating: 54dB(A) or less; Standby: 42dB(A) or less; Power save: 28dB(A) after 30 mins	
Dimensions (HxWxD)	471 x 654.5 x 623mm	
Weight³	C910n: 76kg; C910dn: 81kg	
Duty cycle	Maximum: 150,000 pages/month; Average: 5,000 to 15,000 pages per month	
Warranty	Pan European 1 year on-site	
Product order numbers	C910n: 01268601; C910dn: 01266801	

ACCESSORIES (ORDER NUMBERS)	
2nd/3rd paper tray	42831303
2nd/3rd lockable paper tray	01216601
Duplex	42797203
High Capacity Feeder	42831503
Cabinet	09004256
Memory	256MB: 01182901; 512MB: 01182902
4-tray Finisher	01166701 (High Capacity Feeder required)
5-tray Finisher	01166801 (High Capacity Feeder & 2nd paper tray required)
2-hole Finisher-Punch Unit	42872901 (Finisher unit required)
4-hole Finisher-Punch Unit	42872903 (Finisher unit required)
4-hole (Swedish) Finisher-Punch Unit	42872904 (Finisher unit required)

CONSUMABLES (ORDER NUMBERS)	
Toner cartridges* (15,000 pages)	Cyan: 44036023; Magenta: 44036022; Yellow: 44036021; Black: 44036024
Image drum** (20,000 pages)	Cyan: 44035519; Magenta: 44035518; Yellow: 44035517; Black: 44035520
Transfer Belt (100,000 pages)	42931603
Fuser Unit (100,000 pages)	42931703
Waste Toner Box (30,000 pages)	42869403
Finisher Staples (15,000 staples)	42937603

*Toner: Number of A4 pages @ 5% coverage. Printer shipped with toner for 7,500 pages @ 5%.
**Drum: Average number of A4 pages printed.

OKI SYSTEMS (POLAND) LTD
ul. Domaniewska 42
02-672 Warsaw
Poland
Tel: +48 (0) 22 448 65 00
Fax: +48 (0) 22 448 65 01
WWW.OKI.COM.PL

